

TOOL	Oil Flow/Max.Pressure	Performance	Other Data	Vibrations m/s ²	Noise Level LWA dB	Noise Level LPA dB	Weight
HH10 Breaker	20 l.p.m./160 bar	22 Joule	hex 19x50 mm	7.2	105	94	9,5 kg
HH20 Breaker	20 l.p.m./160 bar	60 Joule	hex 25x108 mm*	4.8	104	93	22 kg
HH23 Breaker	20 l.p.m./160 bar	85 Joule	hex 25x108 mm*	6.2	105	94	23.4 kg
HH23 Breaker	30 l.p.m./160 bar	95 Joule	hex 25x108 mm*	4.4	105	94	23.5 kg
HH25 Breaker	20 l.p.m./160 bar	85 Joule	hex 32x160 mm*	3.6	109	98	25.3 kg
HH25 Breaker	30 l.p.m./160 bar	95 Joule	hex 32x160 mm*	4.5	109	98	25.8 kg
HH27 Breaker	30 l.p.m./160 bar	105 Joule	hex 32x160 mm*	4.4	107	95	27.4 kg
Core Drill	20 l.p.m./170 bar	ø50 - ø200 mm	Std bit 1.1/4"	<2.5	-	<85	7.6 kg
14" Cut-off Saw	20-30 l.p.m./172 bar	137 mm deep	Disc ø360 mm	<2.5	103	92	9.7 kg
16" Cut-off Saw	20-40 l.p.m./172 bar	162 mm deep	Disc ø410 mm	<2.5	104	93	10.5 kg
Water Pump 2"	20 l.p.m./172 bar	40 m ³ /hour	Stone < 38 mm	-	-	-	7.7 kg
Water Pump 3"	20-30 l.p.m./172 bar	80 m ³ /hour	Stone < 63 mm	-	-	-	11 kg
POWERPACK	Oil Flow/Max.Pressure	Engine / POD		Start	Noise Level LWA dB	Noise Level LPA dB	Weight
HPP09	1 x 20 l.p.m./150 bar	Honda 9 HP petrol, POD		Recoil start	101	90	68 kg
HPP13	1 x 20 l.p.m./150 bar or 1 x 30 l.p.m./150 bar	Honda 13 HP petrol, POD		Recoil start	102	91	81 kg
HPP18V	1 x 20-40 l.p.m./150 bar (adjustable)	Vanguard 18 HP petrol		electric start	101	90	105 kg
HPP09E	1 x 20 l.p.m./160 bar	5.5 kw 3x400 V 16A electric			94	83	80 kg
HPP18E	A: 1 x 30 l.p.m./160 bar B: 1 x 40 l.p.m./160 bar	11 kw 3x400 V 32A electric			98	87	105 kg

We reserve the right to alterations without notice. *Other sizes available.

COMBINATION	HPP09	HPP13	HPP18V	HPP09E	HPP18E
HH10 Breaker	●	●	●	●	●
HH20 Breaker	●	●	●	●	●
HH23 Breaker	●	●	●	●	●
HH23 Breaker, 30 l.p.m.	●	●	●	●	●
HH25 Breaker	●	●	●	●	●
HH25 Breaker, 30 l.p.m.	●	●	●	●	●
HH27 Breaker	●	●	●	●	●
Core Drill	●	●	●	●	●
14" Cut-off Saw	●	●	●	●	●
16" Cut-off Saw	●	●	●	●	●
Water Pump 2"	●	●	●	●	●
Water Pump 3"	●	●	●	●	●

● RECOMMENDED ● NOT RECOMMENDED

HYCON - professionals behind the solutions

One of the most experienced teams on the market is behind the HYCON product line. The founders of HYCON have more than half a century experience altogether in the development, production and marketing of quality hydraulic solutions.

Quality and profitability are key words already on the drawing board. This is the reason why HYCON is constantly strengthening its position among the market leaders in this line of business.

The HYCON MANTRA:

"Our most important objective is to develop and produce quality tools that give the customer additional profit for the same or less investment, merely by using HYCON hydraulics as alternative..."



HYCON A/S
Vester Hassingvej 33
DK-9320 Hjallerup
Denmark
Tel: +45 9647 5200
Fax: +45 9647 5201
www.hycon.dk
hycon@hycon.dk



DISTRIBUTOR